



Revillusion®
36" Portrait Built-in
Electric Firebox

RBF36PWC
Weathered Concrete



The Future of
Fireplaces is Clear.™

Building on the innovative Revillusion® ThruView™ full-depth design, the new Weathered Concrete Series strikes a more contemporary chord. The poured concrete features subtle detail and a neutral palette that provides a dramatic contrast for the lifelike flames. This playful use of an industrial material is a unique way to give any space some stylish, industrial flair.



Revillusion® 36" Portrait Built-in Electric Firebox

RBF36PWC Weathered Concrete



RBF36PWC
Weathered concrete
firebox interior



Mood-maker Remote
Customize the light color and intensity for a fireplace that reflects your personality.

120 V | 1,300 W | 4,400 BTU
208 V | 1,975 W | 6,745 BTU
240 V | 2,575 W | 8,794 BTU



Also available in Herringbone Brick - RBF36P

Features

- Revillusion® Flame Technology**
Flames are larger, brighter and more random, appearing from within the logs.
- Mirage™ Flame Panel**
Partially frosted acrylic panel is clearly better than a mirror, showing only dazzling flames and no reflections.
- ThruView™ Full-depth Design**
See clear through the flames to the back of the firebox for a more authentic experience.
- Mood Lighting**
Customize the firebox glow with a choice of warm hues, plus midnight mode.
- Color Enhancement**
Adjust the flame base color to red or blue.
- Realogs® Plus**
A full grate of life-size hardwood-cast logs, tiered for greater depth.
- Full Surround Firebox**
More authentic day or night; 270-degree surround with natural soot markings.
- Brightness and Flicker**
Adjust light level to suit the room and choose flicker effect for enhanced firelight.
- Ambient Light Sensor**
Automatically adjusts firebox light to suit the room day to night.
- Quick and Easy Installation**
Simply frame, wire and finish – no venting, gas lines or safety screens.
- Primary Heat**
Option to use 240 volt supply for up to 8,800 BTU - use as part of primary heating plan; heater also operates without flame and can be deactivated.
- All-season Flames**
Enjoy the unique charm of a fireplace 365 days a year using the flames without the heat.
- Direct-wire**
Designed to be direct-wired to a 120, 208 or 240 volt circuit for a seamless look (optional plug kit available).
- Low Carbon Footprint**
The most sustainable fireplace option; no emissions and 100% efficient.

Model #	Description	Lbs / Kg	UPC	Wty†	Carton Dimensions (WxHxD)		Cube	
					Inches	cm	ft³	m³
RBF36PWC	36" Portrait Built-in Electric Firebox - Weathered concrete interior	81.1 / 36.8	781052 129863	2 yrs.	41-1/4 x 35-7/8 x 15-1/4	104.7 x 91.2 x 38.6	13.0	0.4
RBF36P	36" Portrait Built-in Electric Firebox - Herringbone brick interior	81.1 / 36.8	781052 108165	2 yrs.	41-1/4 x 35-7/8 x 15-1/4	104.7 x 91.2 x 38.6	13.0	0.4
RBFL42BR	Birch Log Set	15 / 6.8	781052 129993	2 yr.	29-7/8 x 17-1/2 x 15	75.9 x 44.1 x 38.1	4.52	0.13
RBFL42FC	Fresh Cut Log Set	15 / 6.8	781052 129986	2 yr.	29-7/8 x 17-1/2 x 15	75.9 x 44.1 x 38.1	4.52	0.13
RBFLPLUG	Plug Kit	0.6 / 0.3	781052 107656	1 yr.	7 x 3 x 4	17.8 x 7.6 x 10.2	0.05	0.00
RBFLGLASS36P	Single Glass Pane	30.3 / 13.7	781052 108028	1 yr.	42-1/8 x 33-3/4 x 4-1/4	104.4 x 85.6 x 10.7	3.4	0.10
RBFLDOOR36P	36" Portrait Glass Door	37.0 / 16.6	781052 108066	1 yr.	41-7/8 x 34-1/2 x 4-5/8	106.3 x 87.7 x 11.6	3.8	0.10

Specifications, finishes and dimensions are subject to change. †Limited warranty. ©2019 Glen Dimplex Americas.

SE-454-R00-072919

Revillusion® 36" Portrait Built-in Electric Firebox

RBF36PWC Weathered Concrete

Accessories



RBFGLOSS36P - 36" Tempered Front Glass
Dimensions:
35-1/8" W x 26-5/8" H x 3/8" D
(89.1 cm x 67.5 cm x 1.1 cm)



RBFDOOR36P - 36" Functional Doors
with Tempered Glass
Dimensions:
39-3/4" W x 31-3/4" H x 1-1/4" D
(101.1 cm x 80.8 cm x 3.7 cm)



RBFPLUG





RBFL42BR - Birch Log Set
Dimensions:
26-1/2" W x 11-1/8" H x 11" D
(67.2 cm x 28.1 cm x 27.9 cm)



RBFL42FC - Fresh Cut Log Set
Dimensions:
26-1/2" W x 11-1/8" H x 11" D
(67.2 cm x 28.1 cm x 27.9 cm)

Framing Dimensions:



NOTE: The materials used for the finished surround must be cut to precise dimensions as the 1/2" (1.3 cm) self trimming flange is only to create a finished appearance.

RBF36P

A	B	C	D	E	F
12-1/2" (31.8 cm)	36-5/8" (93.0 cm)	30-5/8" (77.8 cm)	60" (152.4 cm)	42-1/2" (108.0 cm)	42-1/2" (108.0 cm)